

The drive end (A/O) is designed for easy and quick engagement with the universal instrument handle.

PRODUCT NO'S:
S0010-00 [Complete System with Case]
Individual/Replacement Parts
S0113 [Universal 4" (10,2 cm) Handle]
S0128 [1.5 mm Screw Extractor]
S0116 [2.5 mm Screw Extractor]
S0130 [3.5 mm Screw Extractor]
S0117 [1.5 mm Hex Driver]
S0114 [2.5 mm Hex Driver]
S0115 [3.5 mm Hex Driver]
S0132 [4.0 mm Hex Driver]
S0133 [5.0 mm Hex Driver]
S0136 [2.5 mm Cannulated Hex Driver]
S0137 [3.5 mm Cannulated Hex Driver]
S0138 [4.0 mm Cannulated Hex Driver]
S0139 [5.0 mm Cannulated Hex Driver]
S0118 [Large Cruciform Screwdriver]
S0119 [Small Cruciform Screwdriver]
S0141 [Mini Cruciform Screwdriver]
S0120 [Single Slot Screwdriver]
S0121 [2.2 mm Trephine]
S0122 [3.2 mm Trephine]
S0123 [4.2 mm Trephine]
S0124 [4.7 mm Trephine]
S0125 [7.2 mm Trephine]
S0127 [Universal Extractor – Shaft Only]
S0127-01 [Large Extraction Bolt Body]
S0127-03 [Small Extraction Bolt Body]
S0127-04 [Extractor Wrench]
S0129 [Pick]
S0140 [Cannulated Drive Extension]
9017 [Screw Removal Case Only]
Case Dimensions: 21" x 9.5" x 2.25 (53,4 x 24,1 x 5,7 cm)
(35,4 % 24,1 % 5,7 011)
±/ • =

USA MADE



•

release mechanism

0

Ergonomic, modular handle with two connection points allows for both straight and T-handle orientations

Universal Screw Removal Instrument System

Designed to help remove a variety of screws-solid and cannulated: stripped hex screws, buried screws, partial screws with broken screw heads

Mini

Cruciform

#S0141

Small

Cruciform

#S0119

Standard cruciform screwdrivers in

large, small, and mini, and single slot.

Screwdrivers

Large

Cruciform

#S0118



Screw Extractors

Unique thread design accommodates removal of stripped screws. The instrument "locks" into the screw head and allows removal once engaged. Designed to be used in a counter-clockwise direction.



Solid shaft in all standard hex sizes.



Universal Extraction Bolts

Designed to remove screws with heads partially or completely missing. The cone shaped head fully engages the remaining screw and optimizes the force needed for removal. The bolt is disposable and locks into place using a unique thread design. Designed to be used in a counter-clockwise direction.

2.2 mm 3.2 mm 4.2 mm 4.7 mm 7.2 mm #S0121 #S0122 #S0123 #S0124 #S0125

Trephines

Designed to fit over submerged screws for extraction with minimal bone loss. Extraction is enhanced by the unique tooth design. Designed to be used in a counter-clockwise direction.



Hex Drivers Four sizes with a cannulated shaft for

easier removal of buried screws.

Single

Slot

#S0120

#S0140 **Cannulated Drive** Extension Used when a longer instrument shaft is desired.



which direction is most efficient and comfortable. The quick-connect release mechanism allows for quick interoperative exchange

fragments and bone or tissue from screw head.



ISO 13485:2016 🔤 - CE